

TerraLUX[®] TLE-300

500+ Lumen Flashlight Upgrade

Features

- 600 Lumens of Initial LED Light Output Using the World's Best Quality, High Power LEDs
- 91% Efficient Optics
- Electronically Regulated for Maximum Battery Life
- Over-Temperature Protection Electronics for LED
- Electronic Regulation for Rock Steady Light Output Over a Wide Range of Battery Voltages
- Never Needs Replacing
- Pure White Light
- Rugged Construction



Specifications

- 3.5 V TO 24 V DC, 12 WATT S POWER CONSUMPTION . CURRENT VARIES WITH VOLTAGE TO MAINTAIN CONSTANT POWER.
- 600 LUMENS INITIAL LED LIGHT OUTPUT. MINIMUM 500 LUMENS AT STEADY STATE
- OVER-TEMPERATURE PROTECTION. LIGHT OUTPUT WILL BE REDUCED TO MAINTAIN SAFE LED OPERATING TEMPERATURE. LIGHT OUTPUT IS REDUCED, NOT SHUTDOWN
- 8.4 DEGREE FWHM BEAM FOR LONG THROW DISTANCE. 31 Cd/L CENTRAL BRIGHTNESS. 0.19 LUX AT 100 YARDS AT 600 LUMENS
- USABLE WITH ALKALINE, NiCd, NiMH, LI-ION.
- APPROXIMATELY 1-2 HOUR RUN TIME WITH 4 ALKALINE D-CELLS. NiMH OR NiCd BATTERIES RECOMMENDED FOR MAXIMUM RUNTIME.
- MODELS AVAILABLE FOR MAG INSTRUMENTS 4-6 CELL D-CELL FLASHLIGHTS, MAG INSTRUMENTS RECHARGEABLE FLASHLIGHT AND STREAMLIGHT RECHARGEABLE FLASHLIGHTS. (TLE-300M, TLE-300MR AND TLE-300S, RESPECTIVELY)

TerraLUX is not affiliated with Mag Instrument, Inc., which owns the MAG-LITE[®] and MINI MAGLITE[®] trademarks and the trademark on the shape, style, and overall appearance of the MINI MAGLITE[®] flashlight. Mag Instrument, Inc.'s trademarks are used here only to identify the flashlights with which TerraLUX intends its products to work. TerraLUX's products are not made, endorsed, or sponsored by Mag Instrument, Inc.