

20° Optic White Flexible LED Wall Washer — 24V, 6W/ft, IP67

Part of our Architectural Series, this IP67 RGBW Flexible Wall Washer combines vibrant RGB color-changing light with a dedicated 2700K Warm White channel. Integrated 20° optical lenses create a precise, narrow beam for wall grazing, façade contouring, architectural accents, and dramatic indoor or outdoor lighting.



SPECIFICATIONS

Electrical	24Vdc	IP Rating	IP67
CRI	90+	Beam Angle	20° integrated optic
CCT	2700K, 4000K, 6500K	Max Run	16.4 ft
Lumen/Ft	549 lm/ft	Connection	2.1mm barrel plug on 6-inch lead
LED Density	30 LEDs/m	Mounting	3M adhesive backing
Dimensions	23mm W x 13.5mm H	Dimming	PWM
Cut Increment	Every 1.31 in.	Warranty	1 year limited

CONFIGURATION OPTIONS

SERIES	LEDs/Ft	WIDTH	IP RATING	POWER/WATTs	CCT	CRI	SKU NUMBER
Architectural Series	9	23mm	IP67	6W/ft	2700K	90+	WW-IP6724V23M-W27
Architectural Series	9	23mm	IP67	6W/ft	4000K	90+	WW-IP6724V23M-W40
Architectural Series	9	23mm	IP67	6W/ft	6500K	90+	WW-IP6724V23M-W65

APPLICATIONS



Under Cabinet



Shelf & Display



Cove & Indirect



Task Lighting



Retail



Architectural

BEAM PATTERNS



20° Side View
(White 18W)



20° Front View
Distance to the wall is 50mm[1.97in.]



20° Front View
Distance to the wall is 100mm[3.94in.]



20° Front View
Distance to the wall is 200mm[7.87in.]



20° Front View
Distance to the wall is 300mm[11.8in.]

